













4.0" color screen



ip65













bluetooth





N5S Minke mobile computers







4000 mah

Features

Scan with speed and comfort.

With the N5S Minke in hand, you can capture practically any type of data, from barcodes to NFC. Its megapixel barcode scanning engine is placed at an angle that allows you to scan comfortably, without needing to tilt the screen. The resulting minimal strain allows you to scan comfortably all day long.

Advanced capacitive touch screen.

The 4.0" HD multi-touch capacitive touch screen dynamically adjusts to the current environment. This enables it to work with or without gloves, wet or dry, and with your fingertip or a stylus.

The best in ergonomics.

Engineered to perfect the user experience, the N5S Minke combines great ergonomics and an intuitive keyboard for comfortable all-day scanning. It's a slim and modern device that is easy to hold in one hand. Protruding and easy-to-use keys leave next to no room for error or confusion.

Long-lasting battery life.

The 4000mAh removable battery combined with the latest dynamic power management technology comfortably guarantees a full shift of continuous use.

Built to survive.

Constructed in robust IP65-rated housing, this device was built to survive in a variety of conditions. It is dust-proof and can be used in a wet environment, while also being resistant to drops of up to 1.5m. The result is a mobile computer that promises years of fuss-free operation.



Application Scenarios







inventory



logistics





warehousing

N5S Minke technical specifications

AN Radio PAN Radio D S tional ndard	2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag High precision GPD+AGPS/Beidou System/ GLONASS Charging cradle Battery, AC adapter, USB cable Buckets (MDM), StayLinked (TE) CTA, SRRC, CCC, CE-RED, RoHS, NCC, BSMI, MTBF, IEC2/FDAII, IEC60825-/EN60825-1
AN Radio PAN Radio D S S tional ndard	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag High precision GPD+AGPS/Beidou System/ GLONASS Charging cradle Battery, AC adapter, USB cable
AN Radio PAN Radio D S Stional	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag High precision GPD+AGPS/Beidou System/ GLONASS Charging cradle
AN Radio PAN Radio D S Stional	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag High precision GPD+AGPS/Beidou System/ GLONASS Charging cradle
AN Radio PAN Radio D	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag
AN Radio PAN Radio D	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz Bluetooth 4.0, 3.0+HS, 2.1+EDR 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag
AN Radio	38/39/40/41 802.11 a/b/g/n, 2.4 GHz and 5GHz
	38/39/40/41
aling	IP65
ор	1.5m
ctro Static Discharge (ESD)	±12 kV (air discharge), ±8 kV (direct discharge)
	5% to 95% (non-condensing)
	-30°C to 70°C (-22°F to 158°F)
erating Temperature	-20°C to 55°C (-4°F to 131°F)
Expansion Slot	Micro SD card (max. 32GB)
dio Jack	3.5mm Audio Jack
0	Microphone / speaker
	5V,2A
	4 hours
	Standby: 500 hours; Scanning: 11 hours of continuous operation
	4000 mAh
	Zo keys (side keys) iniciated) Micro USB 2.0
	28 keys (side keys included)
. ,	4", WVGA (800×480) Capacitive touch screen
	330g (including battery)
	172 x 72 x 24.8mm
	Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. OR Code, PDF417, Data Matrix, MaxiCode, ect.
,	
,	16GB
	Quadrente 1.45Gn2 2GB
0 - /	Android 7.0 Quad-core 1.45GHz
nnee ig	ay h panel ad faces ery Type cted Battery Life cted Charge Time Voltage o Jack insion Slot ating Temperature ige Temperature idity



newland-id.com